

## N O T I C E

THIS DOCUMENT HAS BEEN REPRODUCED FROM  
MICROFICHE. ALTHOUGH IT IS RECOGNIZED THAT  
CERTAIN PORTIONS ARE ILLEGIBLE, IT IS BEING RELEASED  
IN THE INTEREST OF MAKING AVAILABLE AS MUCH  
INFORMATION AS POSSIBLE

11  
DOE/NASA/0124-5  
NASA CR-165181  
ERC LIB. 80173

# Small Passenger Car Transmission Test— Dodge Omni A-404 Transmission

(NASA-CR-165181) SMALL PASSENGER CAR  
TRANSMISSION TEST: DODGE OMNI A-404  
TRANSMISSION Final Report (Eaton  
Engineering and Research Center) 355 p  
HC A16/MF A01

N81-15366

Unclass  
29660

CSC L 13F G3/37

M. P. Bujold  
Eaton Corporation  
Engineering & Research Center

September 1980

Prepared for  
National Aeronautics and Space Administration  
Lewis Research Center  
Under Contract DEN3-124

for  
**U.S. DEPARTMENT OF ENERGY**  
**Conservation and Solar Energy**  
**Office of Transportation Programs**



DOE/NASA/0124-5  
NASA CR-165181  
ERC LIB. 80173

**Small Passenger Car  
Transmission Test—  
Dodge Omni A-404 Transmission**

M. P. Bujold  
Eaton Corporation  
Engineering & Research Center  
Southfield, Michigan 48037

September 1980

Prepared for  
National Aeronautics and Space Administration  
Lewis Research Center  
Cleveland, Ohio 44135  
Under Contract DEN3-124

for  
U.S. DEPARTMENT OF ENERGY  
Conservation and Solar Energy  
Office of Transportation Programs  
Washington, D.C. 20545  
Under Interagency Agreement DE-AI01-77CS51044

## PREFACE

The Electric and Hybrid Vehicle Research, Development, and Demonstration Act of 1976 (Public Law 94-413) authorized a Federal program of research and development designed to promote electric and hybrid vehicle technologies. The Energy Research and Development Administration, now the Department of Energy (DOE), which was given the responsibility for implementing the Act, established the Electric and Hybrid Vehicle Research, Development, and Demonstration Project within the Division of Transportation Energy Conservation to manage the activities required by Public Law 94-413.

The National Aeronautics and Space Administration under an Interagency Agreement (Number EC-77-A-31-1044) was requested by ERDA (DOE) to undertake research and development of propulsion systems for electric and hybrid vehicles. The Lewis Research Center was made the responsible NASA Center for this project. The work presented in this report is an early part of the Lewis Research Center program for propulsion system research and development for electric vehicles.

The work described in this report was conducted under Contract DEN3-124 with the National Aeronautics and Space Administration (NASA) and sponsored by the Department of Energy through an agreement with NASA.



# TABLE OF CONTENTS

	<u>PAGE</u>
SUMMARY.....	1
INTRODUCTION.....	2
EQUIPMENT TESTED.....	3
TEST APPARATUS.....	4
TEST PROCEDURES.....	16
TEST RESULTS.....	26
DRIVE PERFORMANCE COVER SHEET.....	27
Drive Performance 1st Gear Input Torque = 10 lb-ft ...	29
"          "          "          "          "          20 lb-ft ...	34
"          "          "          "          "          30 lb-ft ...	39
"          "          "          "          "          40 lb-ft ...	44
"          "          "          "          "          50 lb-ft ...	49
"          "          "          "          "          60 lb-ft ...	54
"          "          "          "          "          70 lb-ft ...	59
"          "          "          "          "          80 lb-ft ...	64
"          "          "          "          "          90 lb-ft ...	69
DRIVE PERFORMANCE COVER SHEET.....	74
Drive Performance 2nd Gear Input Torque = 10 lb-ft ...	76
"          "          "          "          "          20 lb-ft ...	81
"          "          "          "          "          30 lb-ft ...	86
"          "          "          "          "          40 lb-ft ...	91
"          "          "          "          "          50 lb-ft ...	96
"          "          "          "          "          60 lb-ft ...	101
"          "          "          "          "          70 lb-ft ...	106
"          "          "          "          "          80 lb-ft ...	111
"          "          "          "          "          90 lb-ft ...	116
DRIVE PERFORMANCE COVER SHEET.....	121
Drive Performance 3rd Gear Input Torque = 10 lb-ft ...	123
"          "          "          "          "          20 lb-ft ...	128
"          "          "          "          "          30 lb-ft ...	133
"          "          "          "          "          40 lb-ft ...	138
"          "          "          "          "          50 lb-ft ...	143
"          "          "          "          "          60 lb-ft ...	148
"          "          "          "          "          70 lb-ft ...	153
"          "          "          "          "          80 lb-ft ...	158
"          "          "          "          "          90 lb-ft ...	163

# TABLE OF CONTENTS (cont'd)

	<u>PAGE</u>
CROSS SECTIONAL ROAD LOAD PERFORMANCE COVER SHEET.....	168
Cross Sectional Road Load Performance 3rd Gear	
Output Torque = 15 lb-ft ...	170
" " " " 50 lb-ft ...	175
" " " " 80 lb-ft ...	180
" " " " 115 lb-ft ...	185
" " " " 140 lb-ft ...	190
" " " " 175 lb-ft ...	195
" " " " 210 lb-ft ...	200
" " " " 240 lb-ft ...	205
" " " " 280 lb-ft ...	210
COAST PERFORMANCE COVER SHEET.....	215
Coast Performance 1st Gear Converter Torque = 10 lb-ft ...	217
" " " " 20 lb-ft ...	222
" " " " 30 lb-ft ...	227
" " " " 40 lb-ft ...	232
" " " " 50 lb-ft ...	237
" " " " 60 lb-ft ...	242
COAST PERFORMANCE COVER SHEET.....	247
Coast Performance 2nd Gear Converter Torque = 10 lb-ft ...	249
" " " " 20 lb-ft ...	254
" " " " 30 lb-ft ...	259
" " " " 40 lb-ft ...	264
" " " " 50 lb-ft ...	269
" " " " 60 lb-ft ...	274
" " " " 70 lb-ft ...	279
" " " " 80 lb-ft ...	284
COAST PERFORMANCE COVER SHEET.....	289
Coast Performance 3rd Gear Converter Torque = 10 lb-ft ...	291
" " " " 20 lb-ft ...	296
" " " " 30 lb-ft ...	301
" " " " 40 lb-ft ...	306
" " " " 50 lb-ft ...	311
" " " " 60 lb-ft ...	316
" " " " 70 lb-ft ...	321
NO LOAD LOSSES COVER SHEET.....	326
No Load Losses 1st Gear Closed Throttle.....	328
" " 1st Gear Open " .....	330
" " 2nd Gear Closed " .....	332
" " 2nd Gear Open " .....	334
" " 3rd Gear Closed " .....	336
" " 3rd Gear Open " .....	338
APPENDIX.....	A-1

### EQUIPMENT TESTED

This report involves the tests conducted on a 1979 Dodge Omni A-404 automatic transmission (P/N: 4186090 & 151614). The transmission consists of two multiple disc clutches, an overrunning clutch, two servos, a hydraulic accumulator, two bands, and two planetary gear sets to provide three forward ratios and a reverse ratio. The common sun gear of the planetary gear sets is connected to the front clutch by a driving shell which is splined to the sun gear and to the front clutch retainer. The hydraulic system consists of an oil pump, and a single valve body which contains all the valves except the governor valve.

Output torque from the main centerline is delivered through helical gears to the transfer shaft. This gear set is a factor of the final drive (axle) ratio. The shaft also carries the governor and the parking sprag.

An integral helical gear on the transfer shaft drives the differential ring gear. The final drive gearing is completed with the "Federal" (49 states) gear set producing an overall ratio of 3.48:1.

## INTRODUCTION

The Dodge Omni A-404 transmission is a commercially available automatic transmission which is suited for a small passenger car installation. The transmission is equipped with three forward driving ranges, a neutral, reverse, and park. Very little technical information in the area of torque, speed and efficiency data is currently available on this transmission. This lack of available information was the principal reason for the initiation of this test.

The principal object of this test was to map torque, speed, and efficiency curves of the test transmission in each gear range and in both drive performance and coast performance conditions. The test was performed per the specifications of the Passenger Car Automatic Transmission Test Code - SAE J651b. The torque and speed limits of this test were governed by the torque and speed limits of an engine which would typically be supplied with this transmission. The test code specified that three basic tests were to be conducted which involved holding the torque constant and varying the transmission speed. The three specific tests were drive performance, coast performance, and no load losses which were conducted in first, second and third gear.

The test code required that the transmission should be held in gear over the complete range of the test. In order to accomplish this, it was necessary to block the valves. This kept the transmission locked in gear. The test code also specified an oil temperature requirement to ensure that a set viscosity level be attained throughout the tests. This temperature requirement was accomplished through the use of an immersion heater and oil cooler. The oil temperature was the main factor in limiting the amount of load that could be applied to the transmission.

The data that was obtained from the torque and speed sensors was placed directly onto tape. The tape was then fed into a computer which reduced the data and generated the necessary graphs and technical information. The main advantage to this method of data reduction is that any fluctuation that may occur due to system resonance is averaged by the computer. This method minimizes the error and allows the data to be viewed after the tests are completed.

### EQUIPMENT TESTED

This report involves the tests conducted on a 1979 Dodge Omni A-404 automatic transmission (P/N: 4186090 & 151614). The transmission consists of two multiple disc clutches, an overrunning clutch, two servos, a hydraulic accumulator, two bands, and two planetary gear sets to provide three forward ratios and a reverse ratio. The common sun gear of the planetary gear sets is connected to the front clutch by a driving shell which is splined to the sun gear and to the front clutch retainer. The hydraulic system consists of an oil pump, and a single valve body which contains all the valves except the governor valve.

Output torque from the main centerline is delivered through helical gears to the transfer shaft. This gear set is a factor of the final drive (axle) ratio. The shaft also carries the governor and the parking sprag.

An integral helical gear on the transfer shaft drives the differential ring gear. The final drive gearing is completed with the "Federal" (49 states) gear set producing an overall ratio of 3.48:1.

## TEST APPARATUS

The test apparatus used to operate the Dodge Omni A-404 transmission consisted of the following basic items which are described and listed below. The apparatus was basically the same for drive and coast performance tests with the exception of the transmission which was indexed 180° for coast performance tests.

The driving dynamometer was used to power the transmission. A torque sensor was placed on the dynamometer shaft to accurately monitor the torque into the transmission. A speed pickup was placed on the dyno shaft to measure the speed into the transmission.

The output shaft of the transmission was coupled to a torque sensor which accurately measured its torque. The torque sensor shaft was then coupled to a HY-VO chain drive (4:1 ratio) which was coupled to the absorber shaft. The purpose of the chain drive was to increase the slower output shaft speed into a range which would be acceptable to the absorber power requirements. The absorbing dynamometer was used to apply the system load. A speed pickup was mounted to the absorber shaft to measure output speed.

The transmission oil temperature was controlled through the use of a heat exchanger and circulation heater. When the transmission was operating at light load, the oil cooler was shutdown and the circulation heater was engaged so that the oil could be kept up to temperature specification. When the transmission was operating under heavy load, the oil cooler was operating and the circulation heater was disengaged so that the temperature specification was not exceeded.

The transmission was held in first gear by placing the gear selector lever in its appropriate setting. The transmission was held in second gear by blocking the 1 to 2 shift valve in the second position. The transmission was held in third gear by placing stops in the 1 to 2 shift valve and the 2 to 3 shift valve so the valves were kept in the 2 and 3 position respectively.

The transmission differential was locked for the entire test program. This was accomplished by welding the pinion gears to the differential carrier. This allowed the power to flow through one output shaft. This means that the output torques (drive perf.) and input torques (coast perf.) shown in the graphs are twice the values that each wheel would feel. However, the output speeds (drive perf.) and input speeds (coast perf.) are the actual speeds at each wheel.


The instrumentation for the setup consisted of the following basic items. The Lebow torque sensor was used in conjunction with a Daytronic signal conditioner (878). The Himmelstein torque sensor was matched with a Daytronic signal conditioner (878A). The magnetic speed pickup was used with an Airpax speed readout. These signals were then fed into a Sangamo 3500 tape recorder. The tape recorded data were then fed into a Hewlett Packard Analyzer which reduced the data.

DESCRIPTIONPART NO.MANUFACTURER

Driving Dynamometer	Model 26G308	General Electric
Flexible Coupling	226 SN	Thomas-Rexnord
Torque Sensor	MCRT6-02T(2-3)	Himmelstein
Pilot Bearing	SFT-15	Sealmaster
Transmission	A-404	Dodge
Rear Bearing	209-SFF	MRC
Flexible Coupling	226 SN	Thomas-Rexnord
Torque Sensor	1648-5K	Lebow
Torque Sensor	1248-20K	Lebow
Absorber	1014DG	Dynumatic
Heat Exchanger	F-301-ER-2P	Young
Circulation Heater	NWHO-2	Chromalox
Pressure Gage	D-0252	Marsh
HY VO Chain Drive (4:1)	1.25 wide	Morse


INSTRUMENTATION

Torque Signal Conditioner	878A	Daytronic
Torque Signal Conditioner	878	Daytronic
Speed Readout	761400110	Airpax
Temperature Conditioner	810	Daytronic
Thermocouples	6610WBA2	Applied Instruments




**Drive Performance Test Setup  
DEN3-124**







## Coast Performance Test Setup DEN3-124



1979 Dodge Omni Drive Performance - Front View




1979 Dodge Omni Drive Performance - Side View




1979 Dodge Omni Drive Performance - Back View






1979 Dodge Omni Coast Performance - Front View



1979 Dodge Omni Coast Performance - Side View



Control Console with Data Reduction Equipment

## TEST PROCEDURE

The test was conducted per the Passenger Car Automatic Transmission Test Code-SAE J651b. The code states that three basic tests should be performed on the transmission. These tests were drive performance, coast performance and no load losses. Each test was performed to the accuracies stated in the code. The throttle valve was modulated throughout the test to its normal operating positions. The chart on page 22 indicates the engine torque and its related throttle valve setting.

The first test conducted was the drive performance test. The limits of the test were determined by the normal operating conditions of an engine typically supplied with this transmission. The torque limit was set to 90 lb-ft and the speed limit was set to 5000 rpm. The input shaft of the transmission was tested at a torque which ranged from 10-90 lb-ft on the input shaft of the transmission. The torque was incremented by 10 lb-ft for each test. The speed limits of the test ranged from 500 to 4500 rpm on the input shaft of the transmission.

Section 1 of the test code which is labeled Drive Performance - Constant Input Torque was conducted first. The input torque was held at 10 lb-ft and the speed was incremented from 500-4500 rpm. The torque was then set to 20 lb-ft and the transmission was run through the same speed range. This procedure was followed for input torques of 10, 20, 30, 40, 50, 60, 70, 80, and 90 lb-ft. The throttle valve was modulated to match the appropriate input torque for these test ranges. The starting speed was dependent on when the torque could be attained which was characteristic of the torque converter. The data recorded in this test were input and output speed, input and output torque, line pressure, sump temperature, outlet temperature, case hotspot temperature and ambient temperature.

This procedure was performed on the transmission in first, second and third gear range. The transmission was held in each gear through the entire torque and speed range per the explanation given in the test apparatus section of this report.

The next portion of the test to be conducted was the Cross Sectional Road Load Performance Test. This test was conducted in third gear and involved holding the transmission output shaft at a constant torque while varying the input speed. The output torques selected were 15, 50, 80, 115, 140, 175, 210, 240, and 280 lb-ft. The speed range was from 500-4500 rpm on the input shaft. the starting speed was dependent on when the torque could be attained. The throttle valve was modulated throughout the test to match the appropriate engine torque. The data recorded in this test were input and output torque, input and output speed, line pressure, sump temperature, outlet temperature, case hotspot temperature, and ambient temperature.



The No Load Loss portion of the test was performed next. This test was run with the output shaft turning freely. The input torque and speed were recorded for an entire speed range which ran from 500 rpm to 4500 rpm. This test was performed in each gear range by disconnecting the output shaft and allowing it to turn freely.

The parameters recorded in this test were input torque and speed, line pressure, sump temperature, outlet temperature, case hotspot temperature, and ambient temperature.

The final set of tests performed were the coast performance tests. For this test the transmission was oriented in the reverse direction so that the dynamometer drove through the output shaft of the transmission and the power was taken up in the absorber. The test was operated by setting the converter impeller torque at a constant level and varying its speed in the range set by the previous tests. In order to run this test, it was necessary to spin the torque converter shaft at approximately 400 rpm so that the charge pump would generate the line pressure necessary to operate the transmission. The torque and speed ranges of this test were different from the previous tests due to torque converter characteristics. The speed was limited by two conditions. These conditions were the lowest speed necessary to maintain line pressure and the lowest speed at which the torque could be attained. The amount of torque which could be applied to the system was limited by the current limits of the dynamometer controller. The 1st gear coast performance tests reached the current limit at the 60 lb-ft run. This was due to the slow output speed in first gear which was beyond the dynamometer torque speed characteristics. The data recorded during this portion of the test were input and output torque, input and output speed, line pressure, sump temperature, outlet temperature, case hotspot temperature, and ambient temperature. The throttle valve was set to the idle position during the entire test.

The transmission was filled with Dextron II automatic transmission fluid through the entire test schedule. The physical and chemical properties of the transmission fluid were monitored throughout the test. The fluid appeared slightly brown after the second and third gear coast performance tests. This was attributed to the slow charge pump speeds which meant less oil flow for cooling purposes at high torque levels. The fluid was replaced each time the discoloring was noticed. This indicates that care should be taken if this transmission is to be operated in the coast performance mode (regenerative braking) for any length of time. This problem could be solved by setting a minimum charge pump speed at each torque level.

## CALIBRATION

The test apparatus was calibrated before and after a major test. The major components calibrated were the torque sensors and the speed readouts. The torque sensors were calibrated with their respective readouts and attaching cables so that a total system accuracy was obtained. The calibration was performed on the torque sensors by placing them in a hydraulic test stand which applied a torque against the test specimen and a calibrated torque cell simultaneously. The calibrated torque cell is traceable to the National Bureau of Standards (once removed). The calibrated torque cell was used as an indication of the applied load, while the test specimen was the measured load. The torque sensors were calibrated to the limits of the range over which they were to be operated.

The speed readout was an AIRPAX counter (Model No. 761400110) which was calibrated in an operating range from 0 to 4500 rpm. The counter was calibrated with a Hewlett Packard electric counter (Model No. 5245L) used in conjunction with a WWVB frequency comparator (True Time, Inc. Model No. 60-TR). The accuracy of the digital readout was  $\pm 1$  count.

CALIBRATION SHEET

HIMMELSTEIN TORQUE SENSOR #MCRT 6-02T (2-3)

CAL VALUE = 58.0 lb-ft

(Drive performance torque was positive. Direction of torque was clockwise.)

4-28-80

DEN3-124

APPLIED TORQUE (lb-ft)

MEASURED TORQUE (lb-ft)

0.0	0.0
25.0	25.0
50.0	50.0
75.0	75.0
100.0	100.0
125.0	125.0
150.0	150.0
125.0	125.0
100.0	100.0
75.0	75.0
50.0	50.0
25.0	25.5
0.0	0.0

(Coast performance torque was negative. Direction of torque was counterclockwise.)

0.0	-0.5
-25.0	-24.5
-50.0	-49.5
-75.0	-74.5
-100.0	-99.5
-125.0	-124.5
-150.0	-149.5
-125.0	-125.0
-100.0	-100.0
-75.0	-74.5
-50.0	-49.5
-25.0	-24.5
-0.0	-0.0

CALIBRATION SHEET

LEBOW TORQUE SENSOR #1648-5K

CAL VALUE = 271.5 lb-ft

(Drive performance torque was positive. Direction of torque was clockwise.)

5-16-80

DEN3-124

APPLIED TORQUE (lb-ft)

MEASURED TORQUE (lb-ft)

0.0	0.0
50.0	49.0
100.0	99.5
150.0	149.5
200.0	200.0
250.0	250.0
300.0	300.5
350.0	351.0
400.0	401.5
350.0	351.0
300.0	300.5
250.0	250.0
200.0	200.0
150.0	149.5
100.0	99.0
50.0	49.0
0 0	0.0

---

(Coast performance torque was negative. Direction of torque was counterclockwise.)

-0.0	-1.0
-50.0	-52.0
-100.0	-101.5
-150.0	-152.0
-200.0	-202.0
-250.0	-252.0
-300.0	-302.5
-350.0	-352.5
-400.0	-402.0
-350.0	-352.0
-300.0	-302.0
-250.0	-251.0
-200.0	-201.5
-150.0	-151.5
-100.0	-101.0
-50.0	-51.0
-0.0	-0.5

CALIBRATION SHEET  
 LEBOW TORQUE SENSOR #1248-2K  
 CAL VALUE = 479.0 lb-ft  
 (Drive performance torque was positive. Direction of torque was clockwise.)

6-23-80  
 DEN3-124

APPLIED TORQUE (lb-ft)	MEASURED TORQUE (lb-ft)
0.0	0.0
300.0	300.3
600.0	599.8
900.0	898.7
1200.0	1197.2
1500.0	1500.0
1200.0	1199.7
900.0	898.5
600.0	597.6
300.0	297.4
0.0	0.0

---

(Coast performance torque was negative. Direction of torque was counterclockwise.)

-0.0	-0.0
-300.0	-297.4
-600.0	-598.5
-900.0	-899.3
-1200.0	-1199.7
-1500.0	-1500.0
-1200.0	-1198.8
-900.0	-898.5
-600.0	-598.5
-300.0	-298.2
-0.0	-0.0

Following is a table of engine torque vs. throttle cable position. The transmission throttle cable was modulated for each engine torque level throughout the tests.

<u>ENGINE TORQUE (lb-ft)</u>	<u>THROTTLE CABLE POSITION (in.)</u>
closed	.00
10	.07
20	.14
30	.21
40	.28
50	.35
60	.42
70	.49
80	.56
90	.62
open	

## SYSTEM ACCURACY

The instruments used in the test setup have been calibrated to insure the accuracy of the test data. The individual components utilized in the tests contain manufacturers specifications which guarantee the accuracy of the instrumentation. These accuracies are listed and combined in the appendix section to determine the total system accuracy. The three major components involved in the system accuracy are the torque signals, speed signals, and data reduction equipment. Worst case system accuracies for the torque sensors, cabling and readouts were determined from the calibration charts and are shown below.

TAPE RECORDER: Sangamo Model #3500

ACCURACY:  $\pm 0.05\%$  of Full Scale

TORQUE SENSOR: Lebow (1648-5K) + Daytronic (878A)

ACCURACY:  $((\text{Calculated Torque} - \text{Measured}) / \text{Full Scale Torque}) \times (100)$   
 $((175.79 - 176.0) / 416.66) \times (100) = \pm 0.05\%$  of Full Scale

TORQUE SENSOR: Himmelstein (MCRT 6-62T(2-3)) + Daytronic (878)

ACCURACY:  $((\text{Calculated Torque} - \text{measured}) / \text{Full Scale Torque}) \times (100)$   
 $((56.26 - 55.9) / (166.66)) \times (100) = \pm 0.21\%$  of Full Scale

SPEED SENSOR: Speed Pickup + Airpax Counter

ACCURACY: Calibration was  $\pm 1$  Count  $(1/4000) \times (100) = \pm 0.025\%$  of Full Scale

SPEED CONDITIONER (Frequency to Voltage Converter-Daytronic 840)

ACCURACY: 0.05% of Average DC Voltage  $\pm 0.10\%$  of Full Scale

HEWLETT PACKARD ANALYZER (HP 5451B Fourier Analyzer)

ACCURACY: 12 Bits =  $2^{11} = 2048$  Bits = 1 Volt  
 $(1/2048) \times (100) = \pm 0.048\%$  of Full Scale

COMPUTER INTER NUMBER CALCULATION (Method of Program Calculation)  
= 0.5% of Full Scale

The inter number calculation error resulted from the method that the computer used to average the acquired data. This method is explained in the Appendix A.

From the instrument accuracy determined above, a system accuracy may be determined. There are two generally accepted methods for calculating a system error. These methods are the root mean square and the sum of the errors. Both methods are tabulated in the appendix and charted below for torque, speed, power and efficiency readings.

	ROOT MEAN SQUARE METHOD <u>% OF FULL SCALE</u>	SUM OF ERRORS METHOD <u>% OF FULL SCALE</u>	<u>FULL SCALE</u>
Torque Error (Lebow)	0.08%	0.15%	416 lb-ft
Torque Error (Himm.)	0.221%	0.31%	166 lb-ft
Speed Error	0.124%	0.223%	4000 RPM
Power Out Error	0.50%	0.70%	90 HP
Efficiency Error	0.58%	1.0%	100%



## DATA REDUCTION

The signals obtained from the torque and speed transducers of the test stand were placed directly onto a Sangamo Tape Recorder Model No. 3500. The information on the tape was then fed into a computer which was used to compile the data. While in the computer, the data was reviewed to insure their accuracy and then a hard copy was printed out on a line printer.

The following procedure was used to record the input and output torque. The torque signals were placed on the tape recorder as voltage. A calibration value was determined in engineering units (lb-ft) for each torque sensor. The torques were recorded on channels one and two in the following manner:

CHANNEL 1: PRECALIBRATION ZERO    CALIBRATION VOLTAGE    PRERUN  
ZERO    DATA

CHANNEL 2: PRECALIBRATION ZERO    CALIBRATION VOLTAGE    PRERUN  
ZERO    DATA

This information was then fed into the computer which integrated and compiled a 2.5 second sample of data to obtain an average value in engineering units.

The frequency signals from the speed pickups were placed directly onto the tape recorder. The data on the tape was then fed into a frequency to voltage unit which turned the frequency into a dc voltage which in turn was fed into the computer. The method for recording speeds is shown below.

CHANNEL 3: ZERO FREQUENCY    CALIBRATION FREQUENCY    PRERUN ZERO  
FREQUENCY    DATA

CHANNEL 4: ZERO FREQUENCY    CALIBRATION FREQUENCY    PRERUN ZERO  
FREQUENCY    DATA

The data on these channels was then fed into the computer which integrated and compiled a 2.5 second sample of data to obtain an average speed value in engineering units.

The computer was programmed to take the values of torques and speeds and calculate efficiency and power from them. From the data it has generated, the computer would print out the required graphs and data per the contract specification. The main advantage to taking data in this manner was that the computer would calculate an integrated average which would minimize the error in a fluctuating signal. Any fluctuation due to system resonance or gear teeth meshing would be integrated and averaged.

## TEST RESULTS

The data contained in this segment of the report has been divided into three major sections. These sections are drive performance, coast performance, and no load losses. There are five data sheets for each test condition in the drive performance and coast performance tests. The organization of this data is described and listed in the table of contents. Cover sheets for drive performance, coast performance and no load losses have been placed at the beginning of each section to describe the enclosed sheets.

DRIVE PERFORMANCE

1st Gear

## <sup>28</sup>Graphs Contained in This Section

**Torque Ratio -vs- Output Speed**

**Output Torque -vs- Output Speed**


**Input Speed -vs- Output Speed**

**Efficiency -vs- Output Speed**

**Efficiency -vs- Power Out**

**Torque In**

**Speed In**





**Torque Out**


**Speed Out**


---

**Drive Performance Tests**


















EFFICIENCY %












ORIGINAL PAGE IS  
 OF POOR QUALITY








TORQUE RATIO 10:1
















EFFICIENCY %















































EFFICIENCY :

















EFFICIENCY %


TOPOQUE RATIO 10:11














EFFICIENCY %





EFFICIENCY %

TORQUE RATIO  $T_o/T_i$














EFFICIENCY %

DRIVE PERFORMANCE


2nd Gear

## Graphs Contained in This Section

Torque Ratio -vs- Output Speed  
Output Torque -vs- Output Speed  
Input Speed -vs- Output Speed  
Efficiency -vs- Output Speed  
Efficiency -vs- Power Out


Torque In


Speed In





Torque Out


Speed Out



































TORQUE RATIO 10/11



















TORQUE RATIO 10/11
































































TORQUE RATIO 10/11




























**DRIVE PERFORMANCE**

**3rd Gear**


## Graphs Contained in This Section

122

Torque Ratio -vs- Output Speed  
Output Torque -vs- Output Speed  
Input Speed -vs- Output Speed  
Efficiency -vs- Output Speed  
Efficiency -vs- Power Out

Torque In

Speed In




Torque Out


Speed Out


---


**Drive Performance Tests**




TORQUE RATIO 10/11













EFFICIENCY %














































EFFICIENCY %





TORQUE RATIO  $T_o/T_i$






































TORQUE RATIO 10/11










EFFICIENCY %
































CROSS SECTIONAL ROAD LOAD PERFORMANCE

3rd Gear



## Graphs Contained in This Section

**Torque Ratio -vs- Output Speed**

**Output Torque -vs- Output Speed**


**Input Speed -vs- Output Speed**

**Efficiency -vs- Output Speed**

**Efficiency -vs- Power Out**

**Torque In**

**Speed In**





**Torque Out**


**Speed Out**


---


**Drive Performance Tests**















EFFICIENCY %






































TORQUE RATIO 10/11










EFFICIENCY %


















EFFICIENCY %





TORQUE RATIO  $T_o/T_i$















EFFICIENCY %





















TORQUE RATIO 10/11


























**COAST PERFORMANCE**

**1st Gear**

## Graphs Contained in This Section

**Torque Ratio -vs- Output Speed**

**Output Torque -vs- Output Speed**


**Input Speed -vs- Output Speed**

**Efficiency -vs- Output Speed**

**Efficiency -vs- Power Out**

**Torque In**

**Speed In**



**Torque Out**


**Speed Out**

---


## **Coast Performance Tests**





TORQUE RATIO  $T_o/T_i$





ORIGINAL PAGE IS  
OF POOR QUALITY









































EFFICIENCY


















EFFICIENCY %




TORQUE RATIO  $T_o/T_i$



























EFFICIENCY %



## COAST PERFORMANCE

2nd Gear

## Graphs Contained in This Section

**Torque Ratio -vs- Output Speed**

**Output Torque -vs- Output Speed**


**Input Speed -vs- Output Speed**

**Efficiency -vs- Output Speed**

**Efficiency -vs- Power Out**

**Torque In**

**Speed In**




**Torque Out**


**Speed Out**


---


**Coast Performance Tests**


















EFFICIENCY %



























































































INPUT SPEED RPM
















7-7







**COAST PERFORMANCE**

**3rd Gear**

## Graphs Contained in This Section

**Torque Ratio -vs- Output Speed**


**Output Torque -vs- Output Speed**

**Input Speed -vs- Output Speed**

**Efficiency -vs- Output Speed**

**Efficiency -vs- Power Out**


**Torque In**  
**Speed In**





**Torque Out**  
**Speed Out**


---


**Coast Performance Tests**















EFFICIENCY %
































































































EFFICIENCY

## Graphs Contained in This Section

**Torque Loss -vs- Input Speed**

Torque In


Speed In



---


**No Load Losses**

**NO LOAD LOSSES**  
**1st Gear (Closed Throttle)**







NO LOAD LOSSES  
1st Gear (Open Throttle)




**NO LOAD LOSSES**  
**2nd Gear (Closed Throttle)**



NO LOAD LOSSES  
2nd Gear (Open Throttle)




NO LOAD LOSSES  
3rd Gear (Closed Throttle)





NO LOAD LOSSES  
3rd Gear (Open Throttle)



## **APPENDIX**

**ROOT MEAN SQUARE METHOD**

$$\begin{aligned}\text{TORQUE ERROR (HIMMELSTEIN)} &= \sqrt{(\text{TORQUE TRANS. ERROR})^2 + (\text{TAPE RECORDER ERROR})^2 + (\text{ANALYZER ERROR})^2} \\ &= \sqrt{(0.21)^2 + (0.05)^2 + (0.048)^2} = \underline{\pm 0.221\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{TORQUE ERROR (LEBOW)} &= \sqrt{(\text{TORQUE TRANS. ERROR})^2 + (\text{TAPE RECORDER ERROR})^2 + (\text{ANALYZER ERROR})^2} \\ &= \sqrt{(0.05)^2 + (0.05)^2 + (0.046)^2} = \underline{\pm 0.08\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{SPEED ERROR} &= \sqrt{(\text{SPEED SENSOR})^2 + (\text{SPEED CONDITIONER})^2 + (\text{TAPE RECORDER ERROR})^2 + (\text{ANALYZER ERROR})^2} \\ &= \sqrt{(0.025)^2 + (0.10)^2 + (0.05)^2 + (0.048)^2} = \underline{\pm 0.124\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{POWER OUT ERROR} &= \sqrt{(\text{TORQUE ERROR (LEBOW)})^2 + (\text{SPEED ERROR})^2 + (\text{COMPUTER CALCULATION ERROR})^2} \\ &= \sqrt{(0.08)^2 + (0.124)^2 + (0.5)^2} = \underline{\pm 0.5\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{EFFICIENCY ERROR} &= \sqrt{(\text{TORQUE ERROR (LEBOW)})^2 + (\text{SPEED ERROR})^2 + (\text{TORQUE ERROR (HIMM)})^2 + (\text{SPEED ERROR})^2} \\ &\quad + (\text{COMPUTER CALCULATION ERROR})^2 \\ &= \sqrt{(0.08)^2 + (0.124)^2 + (0.221)^2 + (0.124)^2 + (0.5)^2} = \underline{\pm 0.579\% \text{ of Full Scale}}\end{aligned}$$

**SUM OF ERROR METHOD**

$$\begin{aligned}\text{TORQUE ERROR HIMMELSTEIN} &= (\text{TORQUE TRANSDUCER ERROR}) + (\text{TAPE RECORDER ERROR}) + (\text{ANALYZER ERROR}) \\ &= (0.21) + (0.05) + (0.048) = \underline{\pm 0.308\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{TORQUE ERROR (LEBOW)} &= (\text{TORQUE TRANS. ERROR}) + (\text{TAPE RECORDER ERROR}) + (\text{ANALYZER ERROR}) \\ &= (0.05) + (0.05) + (0.046) = \underline{\pm 0.146\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{SPEED ERROR} &= (\text{SPEED SENSOR}) + (\text{SPEED CONDITIONER}) + (\text{TAPE RECORDER ERROR}) + (\text{ANALYZER ERROR}) \\ &= (0.025) + (0.1) + (0.05) + (0.048) = \underline{\pm 0.223\% \text{ of Full Scale (1 Volt = 4000 RPM)}}\end{aligned}$$

$$\begin{aligned}\text{POWER OUT ERROR} &= (\text{TORQUE ERROR (LEBOW)}) + (\text{SPEED ERROR}) + (\text{COMPUTER CALCULATION ERROR}) \\ &= (0.06) + (0.124) + (0.5) = \underline{\pm 0.704\% \text{ of Full Scale}}\end{aligned}$$

$$\begin{aligned}\text{EFFICIENCY ERROR} &= (\text{TORQUE ERROR (LEBOW)}) + (\text{SPEED ERROR}) + (\text{TORQUE ERROR HIMM.}) + (\text{SPEED ERROR}) \\ &\quad + (\text{COMPUTER CALCULATION ERROR}) \\ &= (0.08) + (0.124) + (0.221) + (0.124) + (0.5) = \underline{\pm 0.1049\% \text{ of Full Scale}}\end{aligned}$$

The inter number computer calculation error was determined by taking a set of sample calculations and comparing the accurate multiplication to the computer multiplication. A sample comparison is given below.

DATA DRIVE  
PERFORMANCE  
2ND GEAR

$T_1=40$  lb/ft

ACCURATE CALCULATION      COMPUTER CALCULATION

$T_1=39.500$ ,  $T_0=116.3369$        $T_0/T_1=2.9452$        $T_0/T_1=2.9367$

Comparison =  $(2.9452 - 2.9367)/2.9452 \times 100 = 0.288\%$

Since every calculation was not checked in this manner, a factor of safety was added to 0.288%, and 0.5% was used as the inter number computer calculation error.

## OTHER MANUALS

To locate specific manuals in the documentation shipped with the system, refer to the System Configuration Notice for the contents of each binder.

## SYSTEM SPECIFICATIONS & CHARACTERISTICS

The specifications in Table 1-1 describe the system's warranted performance. Those items under the heading of "Characteristics" go beyond the guaranteed specifications and give typical performance for some additional parameters and operations. These are included only to give you information which may be useful in applying the system.

Table 1-1. System Specifications and Characteristics

### SPECIFICATIONS

(Specifications describe the standard system's warranted performance.)

#### ANALOG-TO-DIGITAL CONVERTER

**Input Voltage Range:**  $\pm 0.125V$  to  $\pm 8V$  peak in steps of 2.  
**Input Coupling:** dc or ac.  
**Input Channels:** 2 channels wired for 4 standard. 4 channels optional with plug-in cards.  
**Resolution:** 12 bits including sign.  
**Input Frequency Range:** dc to 50 kHz, 5 Hz to 50 kHz, ac coupled, 100 kHz optional.  
**Sample Rate:**  
**Internal:** 100 kHz max. 1, 2, 3, or 4 channels simultaneously. 200 kHz optional on 1, 2, 3, or 4 channels. (50 kHz max. 3 or 4 channels simultaneously.†)  
**External:** An external time base may be used to allow external control of the sampling rate up to 100 kHz, 200 kHz optional. One sample can be taken for each clock pulse, TTL level.  
**Internal Clock Accuracy:**  $\pm 0.01\%$ .

#### DISPLAY UNIT

**Vertical Scale Calibration:** Data in memory is automatically scaled to give a maximum on-screen calibrated display. The scale factor is given in volts/division, volts<sup>2</sup>/division, or in dB offset.  
**Log Display Range:** 80 dB with a scale factor ranging from 0 to +998 dB. Offset selectable in 4 dB steps.  
**Linear Display Range:**  $\pm 4$  divisions with scale factor ranging from  $1 \times 10^{-512}$  to  $5 \times 10^{512}$  in steps of 1, 2, and 5.  
**Digital UP/DOWN Scale:** Allows 8 up-scale and 2 down-scale steps, calibrated continuous scale factor.  
**Horizontal Scale Calibration:**  
**Linear Sweep Length:** 10, 10.24 or 12.8 divisions.  
**Log Horizontal:** 0.5 decades/division.  
**Markers:** Intensity markers every 8th or every 32nd point.

#### BASE SOFTWARE

**Transform Accuracy:** The expected rms value of computational error introduced in either the forward or inverse FFT will not exceed 0.1% of the rms value of the transform result.  
**Dynamic Range:** >75 dB for a minimum detectable spectral component in the presence of one full scale spectral component after twenty ensemble averages for a block size of 1024.

#### EXECUTION TIMES\*

**Fourier Transform:** <55 ms  
**Stable Power Spectrum Average:** <80 ms  
**Stable Tri-Spectrum Average:** <220 ms

#### REAL TIME BANDWIDTHS\*

**Fourier Transform:** >7.5 kHz  
**Stable Power Spectrum Average:** 5.4 kHz  
**Stable Tri-Spectrum Average:** 1.9 kHz

#### MASS STORAGE SOFTWARE

##### MAXIMUM REAL TIME DATA ACQUISITION RATE (Single Channel):

**BS 256:** 10 kHz  
**BS 1024:** 39 kHz, 25 kHz†  
**BS 4096:** 80 kHz, 30 kHz†

#### OFF-LINE BSFA SOFTWARE

**Center Frequency Range:** dc to one-half the Real Time Data Acquisition Rate.  
**Center Frequency Resolution:** Continuous resolution to the limit of the frequency accuracy for center frequencies >0.02% of the sampling frequency.  
**Frequency Accuracy:**  $\pm 0.01\%$ .  
**Bandwidth Selection:** In steps of  $f/5n$  where  $n = 2, 3, 4$ , etc.  
**Max. Resolution Enhancement:** >400  
**Dynamic Range:\*\*** 90 dB from peak out-of-band spectral component to the peak level of the passband noise.  
80 dB from peak in-band spectral component to the peak level of the passband noise.  
**Out-of-Band Rejection:** >90 dB  
**Passband Flatness of the Digital Filter:**  $\pm 0.01$  dB

#### ENVIRONMENTAL CONDITIONS

**Temperature Range:** 0°C to 40°C (104°F).

\*For band limited random noise type signals at block size 1024, no display, no Hanning.  
\*\*After eight ensemble averages of a power spectrum at block size 1024. Reduced by 10 dB at the exact center of the band.  
†These rates apply to systems with modules S466B and S4651A-B having a serial prefix lower than 1842.

## **FM RECORD/REPRODUCE SPECIFICATIONS**

<b>Input Sensitivity:</b> .....	0.1 to 2.5 volts rms; adjustable with input attenuator for $\pm 40\%$ deviation. Can be extended to 10 volts.
<b>Nominal Input Level:</b> .....	$\pm 1.4$ volts peak.
<b>Nominal Input Impedance:</b> .....	100 K ohms resistive, shunted by less than 100 pf, unbalanced to ground.
<b>Frequency Response:</b>	
<b>Flat Amplitude Filter</b> .....	DC to 20 KHz, at 60 ips, $\pm 0.5$ db; $\pm 40\%$ deviation.
<b>Linear Phase Filter</b> .....	DC to 12 KHz, at 60 ips, $\pm 0.5$ db; $\pm 40\%$ deviation.
	DC to 20 KHz at 60 ips, $\pm 0.5$ , -3 db; $\pm 40\%$ deviation.
<b>Frequency Responses (Optional):</b> .....	DC to 80 KHz at 120 ips using $\pm 40\%$ deviation with IRIG intermediate band center frequency of 432 KHz. Upper frequency limit and center frequencies are proportionately lower at lower speeds, to 3-3/4 ips. DC to 10 KHz at 60 ips using $\pm 40\%$ deviation with IRIG low band frequency of 54 KHz for improved S/N ratios. Upper frequency limit and center frequencies are proportionately lower at lower speeds.
<b>DC Drift (Oscillator and Discriminator):</b> .....	Less than $\pm 0.5\%$ of peak-to-peak deviation per $10^{\circ}\text{F}$ after 20 minute warm-up.
<b>Signal/Noise Ratio</b> .....	46 db at 60 ips.

DC Linearity: .....	Less than $\pm 0.5\%$ of peak-to-peak deviation reference to best straight line through zero.
AC Distortion: .....	Less than 1.5% total harmonic distortion at all speeds.
Transient Response (60 ips):	
Flat Amplitude Filter ( $\pm 1/2$ db) .....	Rise Time (10% to 90% points) - 22 microseconds. Overshoot - less than 15%.
Linear Phase Filter ( $\pm 1/2$ , -3 db) .....	Rise Time (10% to 90% points) - 18 microseconds. Overshoot - less than 2.5%.
Output Level ( $\pm 40\%$ deviation): .....	$\pm 1.4$ volts peak, into 1000 ohms, with short circuit protection (SCP).
Output Current ( $\pm 40\%$ deviation): .....	$\pm 3$ milliamperes peak with SCP.
Output Impedance: .....	Less than 50 ohms, unbalanced to ground, with SCP.

#### GENERAL

Configuration: .....	One standard 19 inch wide equipment enclosure for 14 channel FM or Direct Record/Reproduce System. For 28-32 vdc operation. Additional enclosure furnished for operation from other power supplies. Optional Rack Mounting Kit available.
Recorder Size (28-32 v): .....	26-1/8 inches high by 19 inches wide by 12 inches deep for a 7 channel-6 speed record/reproduce system or a 14 channel-6 speed record, 2 speed reproduce system. Additional enclosure (7-1/2 inches height) which attaches to portable



# Rotating Shaft Torque Sensors



**Model 1602**

Low capacity torque sensor

Capacity (Oz. in.)	Max. Speed (RPM)	Model	Protected for Overloads to (Oz. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)
50	20,000	1602-50	150	400	.35	3 1/4
100	20,000	-100	300	1,000	.35	3 1/4
200	20,000	-200	600	2,500	.35	3 1/4
500	20,000	-500	1,500	5,500	.35	3 1/4
1,000	20,000	-1K	1,500	8,000	.35	3 1/4

**Models 1604, 1605 & 1607**

Utility rotating shaft  
torque sensor recommended  
for general application.



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for Overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)
50	15,000	1604-50	150	5,000	1.0	18
100	15,000	-100	300	13,500	1.0	18
200	15,000	-200	600	33,000	1.0	18
500	15,000	-500	1,500	85,000	1.0	18
1,000	15,000	-1K	3,000	150,000	1.0	18
2,000	15,000	-2K	6,000	225,000	1.0	18
2,000	15,000	1605-2K	6,000	700,000	3.25	28
5,000	15,000	-5K	15,000	950,000	3.25	28
10,000	15,000	-10K	20,000	1,000,000	3.25	28
20,000	4,000	1607-20K	60,000	6,800,000	52.0	75
50,000	4,000	-50K	150,000	11,800,000	57.0	75
100,000	4,000	-100K	150,000	19,950,000	180.0	75

**Model 1615**

Standard flange drive unit mount with  
AND plate to suit Army, Navy,  
mounting, standard



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for Overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)
50	15,000	1615A-50	150	1,500	1.0	24
100	15,000	-100	300	4,000	1.1	24
200	15,000	-200	600	10,000	1.2	24
500	15,000	-500	1,500	20,000	1.3	24
1K	15,000	-1K	1,500	25,000	1.4	24
50	15,000	1615K-50	75	1,620	1.04	25
100	15,000	-100	150	4,570	1.05	25
200	15,000	-200	300	12,900	1.06	25
500	15,000	-500	750	940,000	1.97	25
1,000	15,000	-1K	1,500	204,000	2.00	25
2,000	15,000	-2K	3,000	347,000	2.08	26
5,000	15,000	-5K	7,500	500,000	2.38	26
10,000	15,000	-10K	15,000	574,000	2.76	26

**Model 1648**

Flange drive units  
recommended for  
use when  
short length is  
mandatory.



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for Overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)
2,000	5,000	1648-2K	3,000	742,000	23.0	23
5,000	5,000	-5K	7,500	1,811,000	23.0	23
10,000	5,000	-10K	15,000	2,248,000	23.0	23
20,000	5,000	-20K	30,000	3,507,000	23.5	23

## GENERAL SPECIFICATIONS: (All Models)

**SENSOR:** Four arm bonded foil strain gage bridge

**BRIDGE RESISTANCE:** 350 ohms nominal

**BRIDGE VOLTAGE:** 20 volts maximum, 3 KHz

**OUTPUT:** 2 to 2.5 millivolt/volt nominal

**LINEARITY:** 0.1% of full scale

**COMPENSATED TEMPERATURE RANGE:** 30°F to 150°F

**USEABLE TEMPERATURE RANGE:** 0°F to 200°F

**EFFECT OF TEMPERATURE ON ZERO:** 0.02% of full scale/°F

**EFFECT OF TEMPERATURE ON OUTPUT:** 0.02% of reading/°F

**Lebow**  
**DEN3-124**

**A-7**

## TECHNICAL SPECIFICATION

# MCRT® 6-02T Non-Contact Torquemeter

MAX. TORQUE—15,000 lb.-in.

SPEED—0-7,500 rpm

### GENERAL DESCRIPTION

The MCRT® 6-02T is a compact, high accuracy, flanged torquemeter well adapted for vehicle drive line measurements and continuous monitoring and feedback applications. It uses a rotating strain gage torque bridge, temperature compensated for drift and modulus. The bridge is connected to a stationary electronic readout via integral, non-contact rotary transformers.

The torquemeter is immune to water, lubricants, coolants, vibration, etc. The elimination of slip rings permits high accuracy low level measurements with long, maintenance free life. Thrust and bending loads are inherently cancelled by the transducer design. An optional, integral non contact speed pickup may be specified when ordering.

*Linearity:* 0.1%

*Temperature Effects:* From 75 to 175° F maximum drift is 0.2% of full scale and maximum error due to modulus change is 0.2% of reading


*Maximum Operating Temperature:* 220° F, assuming permanent lubrication. Above 175° F, the maximum shaft speed may have to be derated.

*Readout:* Any carrier amplifier suitable for strain gage service may be used.

*Excitation Voltage:* 10 volts rms, maximum

*Nominal Output:* 0.75 millivolts/volt (open circuit)

### Standard Ratings



MODEL	FULL SCALE TORQUE (lb.-in.)	TORSIONAL STIFFNESS (lb.-in./rad.)	MAXIMUM BENDING MOMENT (lb.-in.)	MAXIMUM ROTATING INERTIA (in.-oz./sec <sup>2</sup> )	MAXIMUM WEIGHT (lbs.)
MCRT 6-02T					
(1-3)	1,000	602,000	500	0.60	13.8
(2-3)	2,000	1,375,000	1,000	0.60	13.8
(4-3)	4,000	2,640,000	2,000	0.60	13.8
(6-3)	6,000	2,430,000	3,000	0.90	17.0
(10-3)	10,000	2,930,000	5,000	0.90	17.0
(15-3)	15,000	3,530,000	5,500	0.90	17.0

*Overload Capacity:* 2 times full scale rating

*Shaft Speed:* 0 to 7,500 rpm, bidirectional. Optional speed pickup produces 60 pulses per shaft revolution.


*Construction:* Load carrying members (flanges, shaft) are 17-4 PH high strength stainless steel.

### NOTES

[1] Maximum speed rating assumes permanent lubrication. Consult factory for higher speed applications.

[2] When combined axial and bending loads are present, the bending capacity must be derated. Consult factory.

[3] Stator should be compliantly restrained from rotating.



## MODEL 840

# FREQUENCY-TO-VOLTAGE CONVERTER

The Model 840 Frequency-to-Voltage Converter is a conditioner amplifier module that accepts input signals in a wide range of frequencies, wave shapes, and voltage levels and produces standard system output voltages precisely proportional to the frequency or repetition rate of the input signal. It is intended for use in "800" systems for measurement of flow, rpm, and similar phenomena that can be derived from magnetic pickups, turbine flowmeters, or other frequency producing sources.

Nine selectable frequency ranges accommodate virtually all mechanical measurement requirements. An internal crystal oscillator reference and adjustable output span allow precise calibration of the indicating device in terms of frequency, rpm, or any other chosen units appropriate to the particular measurement. In flow measurement, for example, the Model 840 can be used with the Model 890 Digital Indicator and calibrated, using the front panel controls, so as to indicate directly in gallons per minute or gallons per hour, provided only that the flowmeter K Factor (cycles per gallon) is known.\*

The Model 840 is also used in conjunction with the Model 862 Multiplier Module in an instrument that can display torque, rpm, and shaft horsepower in digital engineering units. Additional information on this and other instrument combinations is contained under the Model 862 description.

\* If fluid specific gravity is also known, calibration can be made in units of mass flow, such as Pounds per Hour. For applications where specific gravity is subject to change, corrections can be entered manually on a calibrated dial (see Model 868, p. 46) or applied automatically by a temperature sensing channel (see Model 862, page 42).

## SPECIFICATIONS


### Input:

Type: any AC signal, grounded or floating, irrespective of waveform  
Sensitivity: Three ranges (Lo, Med, & Hi), plus vernier, allow adjustment of threshold level from 5 mv to 50 volts (peak). Maximum continuous input voltage is 25 v, 100 v, & 250 v (RMS), respectively. Input is undamaged by momentary peak voltage of 500 volts on any range. Differential input impedance is 20K ohms, 400K ohms, and 8 Megohms, respectively.  
Common mode rejection: greater than 60 dB to 2 kHz and greater than 30 dB to 100 kHz  
Frequency ranges: 100 Hz, 200 Hz, and 500 Hz, with multipliers of X1, X10, and X100, each with 100% overrange.

### Output:

Standard One Volt Data Signal (see Table One, page 7)  
Standard Ten Volt Output Signal (see Table One, page 7)  
Step function response (to 99% of final value): 800 ms for X1 multiplier, 80 ms for X10 and X100 multipliers  
Step function response (to 99.9% of final value): 2.5 sec for X1 multiplier, 250 ms for X10 and X100 multipliers  
Ripple and noise (max.): less than 0.2% of full scale from 10% to 100% of scale  
Accuracy: 0.05% of scale (based on average value of DC output)  
Housing: standard full width module  
Operating temperature range: +50 to +120 degrees F  
Power requirements: 105-130 volts, 50-400 Hz

PRICE Model 840 Frequency-to-Voltage Converter ..... \$495.00



### Dynamometer Characteristics


#### General Electric

No 1739498  
 Amperes 360  
 Absorbs 125 hp  
 Speeds 2700/6000  
 Torque Arm 15.756

Type TCL-20  
 Volts 250  
 Delivers 75 hp  
 Insts. GE I-7360-B

Class 4-125-2700

# Absorption Model 1014WIG • Speed-Torque Curve



**Dynamatic**  
 DEN3-124

A-11

# SLIP RING TORQUE SENSORS

## Model 1102

Low capacity torque sensors.


## Model 1103



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)	Brush Life Factor - 10*	Ring Diameter (in.)
10	20,000	1103 10	20	112	.01	1/4	NA	NA
20	20,000		40	113	.01	1/4	NA	NA
50	20,000	1102 50	150	685	.676	2	8.2	0.750
100	20,000		300	1,070	.678	2	8.2	0.750
200	20,000		600	1,790	.629	2	8.2	0.750
500	20,000		1,000	3,480	.682	2	8.2	0.750
1,000	20,000	1K	1,500	4,850	.685	2	8.2	0.750

## Models 1104 thru 1109, 1114, 1118 and 1121

Standard rotating shaft torque sensor for general application



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)	Brush Life Factor - 10*	Ring Diameter (in.)
100	16,000	1114-100	300	7,800	1.11	11	25.9	1.187
200	16,000		600	17,200	1.12	11	25.9	1.187
500	16,000		1,000	25,300	1.09	11	25.9	1.187
1,000	16,000		1,500	36,200	1.10	11	25.9	1.187
100	9,000	1104-100	150	6,430	1.52	11	15.4	2.000
200	9,000		300	17,000	1.53	11	15.4	2.000
500	9,000		750	45,200	1.59	11	15.4	2.000
1,000	9,000		1,500	103,000	1.59	11	15.4	2.000
2,000	9,000	2K	3,000	182,500	1.60	11	15.4	2.000
5,000	8,500	1105 5K	7,500	475,000	3.59	28	14.0	2.187
10,000	8,500		15,000	750,000	4.09	28	14.0	2.187
20,000	6,500	1106 20K	30,000	2,610,000	15.18	42	10.2	3.000
50,000	4,000	1107 50K	75,000	7,220,000	53.06	74	7.2	4.250
100,000	4,000		150,000	12,450,000	58.14	74	7.2	4.250
120,000	2,400	1108 120K	180,000	15,400,000	265.41	162	5.3	5.750
240,000	2,400		360,000	23,300,000	285.35	162	5.3	5.750
360,000	2,100	1109 360K	540,000	28,000,000	400.00	240	4.4	7.000
600,000	2,100		600K	40,000,000	577.00	240	4.4	7.000
840,000	450	1118 840K	1,260,000	Consult Factory			3.3	9.000
1,200,000	450		1,800,000	Consult Factory			3.3	9.000
1,800,000	450	1800K	2,700,000	Consult Factory			3.3	9.000
2,400,000	350	1121 2400K	3,600,000	Consult Factory			3.0	10.000
3,000,000	350	3000K	4,500,000	Consult Factory			3.0	10.000

## Model 1115

Flange housing mount with AND pads to match Army-Navy mountings standard Spline drive



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)	Brush Life Factor - 10*	Ring Diameter (in.)
100	24,000	1115A 100	300	5,230	2.44	24	25.9	1.187
200	24,000		600	14,700	2.82	24	25.9	1.187
500	24,000		1,000	25,900	2.43	24	25.9	1.187
1,000	24,000		1,500	37,600	2.44	24	25.9	1.187
100	8,000*	1115K 100	300	5,740	3.01	28	15.4	2.000
200	8,000*		600	19,600	3.49	28	15.4	2.000
500	8,000*		1,000	46,400	3.00	28	15.4	2.000
1,000	8,000*		1,500	103,000	3.01	28	15.4	2.000
2,000	8,000*	2K	3,000	156,000	3.03	28	15.4	2.000
5,000	8,000*	5K	7,500	342,000	3.05	28	15.4	2.000
10,000	8,000*	10K	12,000	420,000	3.25	28	15.4	2.000

\*12,000 RPM with air oil mist lubrication

## Models 1228, 1248, 1241

Flange drive for use when short length is mandatory



Capacity (Lb. in.)	Max. Speed (RPM)	Model	Protected for overloads to (Lb. in.)	Torsional Stiffness (Lb. in./Rad.)	Rotating Inertia (Lb.-in. <sup>2</sup> )	Weight (Lbs.)	Brush Life Factor - 10*	Ring Diameter (in.)
2,000	5,000	1228 2K	3,000	1,455,000	4.38	8	12.7	2.530
5,000	5,000		7,500	2,141,000	4.39	8	12.7	2.530
10,000	5,000	10K	15,000	7,870,000	4.59	8	12.7	2.530
20,000	5,000	1248 20K	30,000	4,647,000	15.53	17	9.4	3.750
50,000	3,000	1241 50K	75,000	12,840,000	193.7	54	6.5	4.750
100,000	3,000	100K	150,000	23,460,000	196.3	54	6.5	4.750

Specifications	Standard	"N" Option	Specifications	Standard	"N" Option
Output at rated capacity millivolts per volt nominal	2 to 2.5	5	Temperature effect on output of reading per °F	0.002%	0.003%
Nonlinearity of rated output	0.1%	0.15%	Temperature effect on zero at rated output per °F	0.002%	0.003%
Hysteresis of rated output	0.1%	0.15%	Excitation voltage maximum volts DC or AC rms	20	20
Repeatability of rated output	0.05%	0.07%	Insulation resistance bridge case megohms at 50 VDC	5000	5000
Zero balance of rated output	1.0%	1.0%	Number of bridges	1	1
Bridge resistance ohms nominal	350	350			
Temperature range compensated °F	70 to 170	70 to 170			
Temperature range useable °F	65 to 200	65 to 200			

**LEDOW**  
**DEN3-124**